

L.N. 307 of 2008**PRODUCT SAFETY ACT
(CAP. 427)****Restriction of Use of Hazardous Substances in Electrical and Electronic Equipment (Amendment) (No. 2) Regulations, 2008**

IN exercise of the powers conferred by articles 38 and 39 of the Product Safety Act, the Minister of Finance, the Economy and Investment, on the advice of the Malta Standards Authority, has made the following regulations:–

1. (1) The title of these regulations is the Restriction of Use of Hazardous Substances in Electrical and Electronic Equipment (Amendment) (No.2) Regulations, 2008 and they shall be read and construed as one with the Restriction of Use of Hazardous Substances in Electrical and Electronic Equipment Regulations, 2004, hereinafter referred to as “the principal regulations.”

Citation, commencement and scope.

L.N. 396 of 2004.

(2) These regulations implement the requirements of Commission Decision of 24 January 2008 amending, for the purposes of adapting to technical progress, the Annex to Directive 2002/95/EC of the European Parliament and of the Council as regards exemptions for applications of lead and cadmium.

(3) These regulations shall be deemed to have come into force on the 1st July, 2006.

2. For Schedule I to the principal regulations there shall be substituted the following:

Substitutes Schedule I to the principal regulations.

“Schedule I

(Regulation 4(2))

Applications of lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE) which are exempt from the requirements of regulation 4(2)

Item No.	Application						
1.	Mercury in compact fluorescent lamps not exceeding 5 mg per lamp.						
2.	Mercury in straight fluorescent lamps for general purposes not exceeding: <table border="0" data-bbox="408 913 1241 1021"> <tr> <td data-bbox="408 913 624 947">— halophosphate</td> <td data-bbox="1129 913 1241 947">10 mg</td> </tr> <tr> <td data-bbox="408 947 855 981">— triphosphate with normal lifetime</td> <td data-bbox="1129 947 1241 981">5 mg</td> </tr> <tr> <td data-bbox="408 981 823 1014">— triphosphate with long lifetime</td> <td data-bbox="1129 981 1241 1014">8 mg.</td> </tr> </table>	— halophosphate	10 mg	— triphosphate with normal lifetime	5 mg	— triphosphate with long lifetime	8 mg.
— halophosphate	10 mg						
— triphosphate with normal lifetime	5 mg						
— triphosphate with long lifetime	8 mg.						
3.	Mercury in straight fluorescent lamps for special purposes.						
4.	Mercury in other lamps not specifically mentioned in this Schedule.						
5.	Lead in glass of cathode ray tubes, electronic components and fluorescent tubes.						
6.	Lead as an alloying element in steel containing up to 0,35 % lead by weight, aluminium containing up to 0,4 % lead by weight and as a copper alloy containing up to 4 % lead by weight.						
7.	(a) Lead in high melting temperature type solders (i.e. tin-lead solder alloys containing more than 85 % lead), (b) Lead in solders for servers, storage and storage array systems, network infrastructure equipment for switching, signaling, transmission as well as network management for telecommunications, (c) Lead in electronic ceramic parts (e.g. piezoelectronic devices).						
8.	Cadmium and its compounds in electrical contacts and cadmium plating except for applications banned under Directive 91/338/EEC ³ amending Directive 76/769/EEC ⁴ relating to restrictions on the marketing and use of certain dangerous substances and preparations.						

³ OJ L 186, 12.7.1991, p. 59.

⁴ OJ L 262, 27.9.1976, p. 201.

9. Hexavalent chromium as an anti-corrosion of the carbon steel cooling system in absorption refrigerators.
- 9a. Deca BDE for polymeric applications.
- 9b. Lead in lead-bronze bearing shells and bushes.
10. -
11. Lead used in compliant pin connector systems.
12. Lead as a coating material for the thermal conduction module c-ring.
13. Lead and cadmium in optical and filter glass.
14. Lead in solders consisting of more than two elements for the connection between the pins and the package of microprocessors with a lead content of more than 80 % and less than 85 % by weight.
15. Lead in solders to complete a viable electrical connection between semiconductor die and carrier within integrated circuit Flip Chip packages.
16. Lead in linear incandescent lamps with silicate coated tubes.
17. Lead halide as radiant agent in High Intensity Discharge (HID) lamps used for professional reprography applications.
18. Lead as activator in the fluorescent powder (1 % lead by weight or less) of discharge lamps when used as sun tanning lamps containing phosphors such as BSP ($\text{BaSi}_2\text{O}_5:\text{Pb}$) as well as when used as speciality lamps for diazo-printing reprography, lithography, insect traps, photochemical and curing processes containing phosphors such as SMS ($(\text{Sr},\text{Ba})_2\text{MgSi}_2\text{O}_7:\text{Pb}$).
19. Lead with PbBiSn-Hg and PbInSn-Hg in specific compositions as main amalgam and with PbSn-Hg as auxiliary amalgam in very compact Energy Saving Lamps (ESL).
20. Lead oxide in glass used for bonding front and rear substrates of flat fluorescent lamps used for Liquid Crystal Displays (LCD).
21. Lead and cadmium in printing inks for the application of enamels on borosilicate glass.

B 4100

22. Lead as impurity in RIG (rare earth iron garnet) Faraday rotators used for fibre optic communications systems.
23. Lead in finishes of fine pitch components other than connectors with a pitch of 0.65 mm or less with NiFe lead frames and lead in finishes of fine pitch components other than connectors with a pitch of 0.65 mm or less with copper lead frames.
24. Lead in solders for the soldering to machined through hole discoidal and planar array ceramic multilayer capacitors.
25. Lead oxide in plasma display panels (PDP) and surface conduction electron emitter displays (SED) used in structural elements; notably in the front and rear glass dielectric layer, the bus electrode, the black stripe, the address electrode, the barrier ribs, the seal frit and frit ring as well as in print pastes.
26. Lead oxide in the glass envelope of Black Light Blue (BLB) lamps.
27. Lead alloys as solder for transducers used in high-powered (designated to operate for several hours at acoustic power levels of 125 dB SPL and above) loudspeakers.
28. Hexavalent chromium in corrosion preventive coatings of unpainted metal sheetings and fasteners used for corrosion protection and Electromagnetic Interference Shielding in equipment falling under category three of Directive 2002/96/EC (IT and telecommunications equipment). Exemption granted until 1 July 2007.
29. Lead bound in crystal glass as defined in Annex I (Categories 1, 2, 3 and 4) of Council Directive 69/493/EEC.⁵
30. Cadmium alloys as electrical/mechanical solder joints to electrical conductors located directly on the voice coil in transducers used in high-powered loudspeakers with sound pressure levels of 100 dB (A) and more.
31. Lead in soldering materials in mercury free flat fluorescent lamps (which e.g. are used for liquid crystal displays, design or industrial lighting).
32. Lead oxide in seal frit used for making window assemblies for Argon and Krypton laser tubes.”.

⁵ OJ L 326, 29.12.1969, p. 36. Directive as last amended by 2003 Act of Accession.’